



### PDKS11GX23

|                                       |             |                         |
|---------------------------------------|-------------|-------------------------|
| Carton Box pieces                     | Qty         | 1                       |
| Product                               |             | Foot Switch             |
| Type                                  |             | with Reset              |
| Feature                               |             | Single                  |
| Contact                               |             | (1NO+1NC)+2NC           |
| Color                                 |             | Yellow                  |
| Protection                            |             | Metal Protection        |
| Current                               | Ie          | 3 A (240V AC)           |
| Usage Category                        |             | AC15                    |
| Mechanical Life                       | Min Qty     | 1000000                 |
| Electrical Life                       | Min Qty     | 100000                  |
| Operating Frequency                   | On-Off/Hour | Mech. 1800 Elec. 1200   |
| Insulation Voltage                    | Ui          | 300 V                   |
| Impulse Withstand Voltage             | Uimp        | 2.5 kV                  |
| Dielectric Strength (Body-Contact)    |             | 2.500V AC               |
| Dielectric Strength (Contact-Contact) |             | 1.500V AC               |
| Isolation Resistance                  |             | 10 MΩ min. (500V DC)    |
| Operating Temperature                 |             | -25 / +80 °C            |
| Pollution Degree                      |             | 3                       |
| Protection Degree                     |             | IP65                    |
| Contact Material                      |             | AgNi                    |
| Cable Section                         |             | 1.5-2.5 mm <sup>2</sup> |
| Screw Torque                          |             | 1.5Nm                   |
| Short Circuit Breaking Capacity       | Ics         | 1 kA                    |
| Body Material                         |             | Plastic                 |
| Production Time                       |             | 31.12.1899 00:00:00     |
| Serial                                |             | PDK Series              |
| Step                                  |             | Double Step             |

|                                                                                                                                                                                                                                                       |                                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
| <b>Specifications</b>                                                                                                                                                                                                                                 | Plastic or Metal options              |
|                                                                                                                                                                                                                                                       | Single and Double Speed               |
|                                                                                                                                                                                                                                                       | Yellow                                |
|                                                                                                                                                                                                                                                       | Grey and orange color options         |
|                                                                                                                                                                                                                                                       | with Latching option                  |
| <b>Standards / Certificates</b>                                                                                                                                                                                                                       | TS EN 60947-5-1    UL 508    VDE 0660 |
|    |                                       |

PDKS11GX23

