

## Datasheet

040X0820-8  
Stainless steel push-button enclosure 82x202x85, undrilled, without cable entry



### Features

|                |                                                                                 |
|----------------|---------------------------------------------------------------------------------|
| Range          | Stainless steel push-button enclosures 82x202 mm                                |
| components     | Undrilled lid                                                                   |
| Code           | 040X0820-8                                                                      |
| Description    | Stainless steel push-button enclosure 82x202x85, undrilled, without cable entry |
| Weight - gr    | 826.0                                                                           |
| Customs Tariff | 85381000                                                                        |
| GTIN           | 8052878048105                                                                   |

### Datasheet

|                                   |                                                   |
|-----------------------------------|---------------------------------------------------|
| Approvals                         | CE                                                |
| Compliance with standards         | IEC-EN62208                                       |
| Operating temperatures            | -40° ÷ +100°C                                     |
| Protection degree                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact         | IK07 (IEC-EN62262)                                |
| Enclosure material                | Stainless steel AISI 316L                         |
| Gasket material                   | Polyurethane foam                                 |
| Screw material                    | Stainless steel AISI 304                          |
| Screw type                        | M5 - cross head Phillips 2                        |
| Tightening torque                 | 2,5Nm (22.1 Lb-in)                                |
| Protection against electric shock | Class I (IEC-EN61140)                             |
| Fitted for outdoor application    | yes                                               |
| Warranty period                   | 18 months                                         |

# Technical drawings

